Giving Shape to Ideas





bizhub 958

With 95 ppm print/copy output in high-resolution B&W, standard dual scanning at up to 240 opm, multiple finishing options and enhanced touch-and-swipe $\,$ interface, the bizhub 958 brings maximum productivity to high-volume document demands and in-house, on-demand printing applications.

System Overview		
System memory	4 GB	
System hard disk	250 GB	
Interface	10-BASE-T/100-BASE-TX/1,000-BASE-T Ethernet, USB 2.0,	
2	Wi-Fi 802.11 b/g (opt.)	
Network protocols	TCP/IP (IPv4/IPv6), NetBEUI, SMB, LPD, IPP, SNMP, HTTP	
Frame types	Ethernet 802.2, Ethernet 802.3, Ethernet II, Ethernet SNAP	
Dual scan	Up to 300 originals / 5.5" x 8.5" to 11" x 17" / 35–210 gsm	
document feeder		
Printable paper size	Scanning/Copying: up to 11" x 17"	
	Printing: up to 11" x 17" full bleed on 12" x 18" paper	
	Custom paper sizes	
	Banner paper max.: 11.75" x 47.25"	
Printable	52–300 gsm	
paper weight	Character of 2 CCO about A Many C CCO about	
Paper input capacity	Standard: 3,650 sheets / Max.: 6,650 sheets	
Tray 1	500 sheets / 5.5" x 8.5" to 12" x 18" / 52–256 gsm	
Tray 2	500 sheets / 5.5" x 8.5" to 12" x 18" / 52–256 gsm	
Tray 3	1,500 sheets / 8.5" x 11" / 52–256 gsm	
Tray 4	1,000 sheets / 8.5" x 11" / 52–256 gsm	
Large capacity tray	3,000 sheets / 8.5" x 11" / 52-256 gsm	
LU-303 (optional)	2.500 -1	
Large capacity tray	2,500 sheets / 8.5" x 11" to 12" x 18" / 52–256 gsm	
LU-205 (optional)	150 also aks / All y Cll to 12ll y 10ll / ayakana nanayainaa /	
Manual bypass	150 sheets / 4" x 6" to 12" x 18" / custom paper sizes / 52–300 gsm	
Automatic duplexing	5.5" x 8.5" to 12" x 18" / 52–256 gsm	
Finishing modes	Offset, group, sort, staple, punch, post insertion,	
-	z-fold, half-fold, tri-fold, booklet	
Output capacity	Max. with finisher: 3,200 sheets	
	Max. without finisher: 250 sheets	
Stapling (optional)	Max.: 100 sheets or 94 sheets + 2 cover sheets	
	(up to 209 gsm)	
Stapling output	Max.: 1000 sheets	
capacity		
Tri-fold	Up to 3 sheets	
Tri-fold capacity	Max.: 30 sheets (tray), unlimited	
Booklet	Max.: 20 sheets or 19 sheets + 1 cover sheet	
	(up to 209 gsm)	
Booklet output	Max.: 100 sheets (tray), unlimited	
capacity		
Copy/print volume	Max.: 300,000 pages/month ¹	
Tonerlifetime	Black: 40,800 pages	
Imaging unit lifetime	400,000 pages / 1,200,000 pages (Developer)	
Power consumption	208 V / 60 Hz, less than 3.8 kW (system)	
System dimensions	26.4" x 32.3" x 48.5" (W x D x H)	
System weight	Approx. 441 lb.	
Drinton Considiration		
Printer Specification	15	

Print resolution	1,800 x 600 dpi, 1,200 x 1,200 dpi		
PDL	PCL6 (XL 3.0), PCL5c, PostScript 3 (ver. 3016), XPS		
Operating systems	Windows (x32/x64): Vista / 7 / 8 Windows Server: 2008 ³ / 2008 R2 / 2012 / 2012 R2 Macintosh OS X 10.6 / 10.7 / 10.8 / 10.9 / 10.10 UNIX / Linux / Citrix		
Printer fonts	80 PCL Latin, 137 PostScript 3 emulation		
Print functions	Direct Print of PCL, PS, TIFF, XPS, PDF (v.17), encrypted PDF files and OOXML (DOCX, XLSX, PPTX), mixmedia and mixplex, "Easy Set" job programming, overlay, watermark, copy protection, carbon copy print		

Copier Specifications

Copying process	Electrostatic laser copy, tandem, indirect	
Toner system	Simitri® HD ^E Polymerized Toner	
Print speed	Up to 95 ppm (Portrait)	
(8.5" x 11")		
Autoduplex speed	Up to 95 ppm (Portrait)	
(8.5" x 11")		
1st copy out time	3.2 sec.	
Warm-up time	Approx. 55 sec. ²	
Copy resolution	600 x 600 dpi	
Gradations	256 gradations	
Multi-copy	1-9,999	
Original format	Up to 11" x 17"	
Magnification	25-400% in 0.1% steps, auto zooming	
Chapter, cover and page insertion, proof copy and screen), adjustment test print, digital art fu job setting memory, poster mode, image reproverlay, stamping, copy protection		

Scanner Specifications

Scan speed	B&W / Color: up to 240 ipm	
Scan resolution	Max.: 600 x 600 dpi	
Scan modes Scan-to-Email, Scan-to-SMB, Scan-to-FTP, S Scan-to-USB, Scan-to-WebDAV, Scan-to-DF TWAIN scan		
File formats	JPEG, TIFF, PDF, PDF/A 1a and 1b (optional), compact PDF, encrypted PDF, searchable PDF (optional), XPS, compact XPS, PPTX, searchable PPTX (optional), searchable DOCX/XLSX (optional)	
Scan destinations	2,100 (shared with fax), LDAP support	
Scan functions	Annotation (text/time/date) for PDF, up to 400 job programs, real time scan preview	

Fax Specifications

Fax	Super G3 (optional)	
Transmission	Analog, i-Fax, Color i-Fax, IP-fax	
Resolution	Max.: 600 x 600 dpi (ultra-fine)	
Compression	MH, MR, MMR, JBIG	
Modem	Up to 33.6 Kbps	
Destinations	2,100 (single + group)	
Functions	Polling, time shift, PC-fax, receipt to confidential box,	

User Box Specifications

Storable documents	Max.: 3,000 documents or 10,000 pages	
Type of user boxes	Public	
	Personal (with password or authentication)	
	Group (with authentication)	
Type of system boxes	Secure print, encrypted PDF, fax receipt, fax polling	
User box functionality	Reprint, combination, download, sending	
	(Email/FTP/SMB and fax), copy box-to-box	

	tures

Security	ISO 15408 EAL33		
-	IEEE 2600.13		
	IP filtering and port blocking		
	SSL2, SSL3 and TSL1.0 network communication		
	IPsec support		
	IEEE 802.1x support		
	User authentication		
	Authentication log		
	Secure print		
	Hard disk overwrite (8 standard types)		
	Hard disk data encryption (AES 256)		
	Hard disk mirroring (opt.)		
	Memory data auto deletion		
	Confidential fax receipt		
	Print user data encryption		
	Copy protection (Copy Guard, Password Copy) (opt.)		
Accounting	Up to 1,000 user accounts		
	Active Directory support		
	(user name + password + Email + SMB folder)		
	User function access definition		
	Optional Biometric authentication (finger vein scanner)		
	Optional ID card authentication (ID card reader)		
Software	PageScope Net Care Device Manager		
	PageScope Data Administrator		
	PageScope Box Operator		
	PageScope Direct Print		
	Print Status Notifier		
	Driver Packaging Utility		
	Log Management Utility		

Maximum monthly duty cycle describes the maximum number of pages a device can output on a monthly basis. This specification is a guideline intended to offer a comparison of durability as it relates to the entire Konica Minolta MFP and printer product line so that the appropriate device can be placed in order to meet customer needs

0			10	
Com	poner	nts and	ı Upi	ions

Components and Op	tions	
AU-102 Biometric	Finger vein scanner	
authentication	50 (C. 19) (C.	
AU-205H Universal	Various ID card technologies	
ID card reader		
EK-610 USB I/F kit	USB keyboard connection	
EK-611 USB I/F kit	USB keyboard connection, Bluetooth	
FK-515 Fax board	Super G3 fax, digital fax functionality, lines 3 & 4 support	
FK-516 Fax board		
FS-536 Staple finisher	Super G3 fax, digital fax functionality	
FS-536SD	50-sheet stapling, 3,200 sheets max. output	
Booklet finisher	50-sheet staple finisher, 20-sheet booklet finisher,	
	2,200 sheets max. output	
FS-537 Staple finisher	100-sheet stapling, 3,200 sheets max. output	
FS-537SD	100-sheet stapling, 20-sheet booklet finisher,	
Booklet finisher	2,500 sheets max. output	
HD-524 Hard	Back-up HDD	
disk mirroring		
JS-602 Job	Separation for fax output, etc.	
separator for FS-537		
Keyboard	External keyboard (requires KH-102)	
KH-102	To place USB keyboard	
Keyboard holder	200 CO	
KP-101 10-Key pad	For use instead of touchscreen	
LK-102 v3	PDF/A, PDF encryption, digital signature	
PDF enhancements		
LK-104 v3	Provides voice guidance functions	
Voice guidance	· · · · · · · · · · · · · · · · · · ·	
LK-105 v3	Searchable PDF	
OCR text recognition	ocardinable (b)	
LK-106	Supports native barcode printing	
Barcode fonts	Supports native barcode printing	
LK-107	Supports native Unicode printing	
Unicode fonts	Supports native officode printing	
LK-108	Cupports native OCR A and B fant printing	
OCR A and B fonts	Supports native OCR A and B font printing	
LK-110 Enhanced	Comments of the formation of DOCK VICK	
	Generates various file formats incl. DOCX, XLSX	
image support	and combines LK-102 (encrypted PDF) + LK-105	
IV 111	(searchable PDF/OCR functionality)	
LK-111	Print data compression for reduced network impact	
ThinPrint® Client		
LU-205	8.5" x 11" to 12" x 18", 2,500 sheets, 52–256 gsm	
Large capacity tray		
LU-303	8.5" x 11", 3,000 sheets, 52–256 gsm	
Large capacity tray		
MK-735 Mount kit	Installation kit for ID card reader	
MK-742 Mount kit	Installation kit for FK-515 fax board	
OT-508 Output tray	Output tray used instead of finisher	
PI-507 Post inserter	Cover insertion, post finishing	
for FS-537		
PK-520 Punch kit	2/3-hole punching, autoswitching	
for FS-536		
PK-523 Punch kit	2/3-hole punching, autoswitching	
for FS-537		
RU-515 Relay unit	Required for the FS-537/FS-537SD	
	and FS-536/FS-536SD	
SC-508 Security kit	Copy Guard function (2x required)	
UK-212	Wireless LAN to network connector	
UK-501 Multi-feed	Detects multi-feeding in the document feeder	
detection kit	become record in the document record	
WT-506 Working table	Authentication device placement	
WT-513 Working table	Used to mount the control panel in an upright position	
ZU-609 Z-fold unit	Z-fold for 11" x 17" prints, 2/3-hole punching	
for FS-537		

 $^{^{2}\}mbox{Warm-up}$ time may vary depending on the operating environment and usage

³ Certification pending



Partnership.

Konica Minolta can help give shape to your ideas and partner with you to achieve your corporate objectives. Contact us to realize opportunities in:

Information Management	IT Services	Technology
Enterprise Content Management (ECM)	Application Services	Office Multifunction Business Solutions
Document Management	Cloud Services	Commercial and Production Printers
Automated Workflow Solutions	IT Security	3D Printers
Business Process Automation	Managed IT Services	Wide Format Printers
Security and Compliance	IT Consulting & Projects	Laptops, Desktops and Computer Hardware
Mobility		Servers and Networking Equipment
		Managed Print Services (MPS)
		Managed Enterprise Services

© 2016 KONICA MINOLTA BUSINESS SOLUTIONS U.S.A., INC. All rights reserved. Reproduction in whole or in part without written permission is prohibited. KONICA MINOLTA, the KONICA MINOLTA logo, bizhub and Giving Shape to Ideas are registered trademarks or trademarks of KONICA MINOLTA, INC. All other product and brand names are trademarks or registered trademarks or organizations. All features and functions described here may not be available on some products. Design & specifications are subject to change without notice.



KONICA MINOLTA BUSINESS SOLUTIONS U.S.A., INC. 100 Williams Drive, Ramsey, New Jersey 07446

CountOnKonicaMinolta.com







Item #: 958SS 6/2016-C